

# **SAFETY DATA SHEET**

Waste Water

## Section 1. Identification

Product name : Waste Water
Product code : Not available.
Synonyms : Sewer Water

Relevant identified uses of the substance or mixture and uses advised against

Product use : Intermediate.

Area of application : Industrial applications.

**Manufacturer** : HF Sinclair

2828 North Harwood

Suite 1300

Dallas, Texas 75201

USA

Customer Service: (214) 954-6720

Emergency telephone : CHEMTREC® (800) 424-9300

number CCN 201319

## Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for

employees and other users of this product.

Classification of the substance or mixture

: Not classified.

**GHS label elements** 

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.
Hazards not otherwise : None known.

classified

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Date of issue/Date of revision: 08/24/2021Date of previous issue: 03/22/2018Version: 31/12

Waste Water HF Sincla					
Ingredient name	Other names	%	CAS number		
water ammonia, anhydrous Sulfide phenol benzene	- - - -	0 - 100 0 - 0.0025 0 - 0.0005 0 - 0.0005 0 - 0.0002	7732-18-5 7664-41-7 15035-72-0 108-95-2 71-43-2		

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

## Description of necessary first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes.

Get medical attention if symptoms occur.

**Ingestion**: Do not induce vomiting unless directed to do so by medical personnel. Wash out mouth

with water. Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical attention if symptoms occur.

## Most important symptoms/effects, acute and delayed

## Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Ingestion : Material not being potable, and contains microorganisms/bacteria that could make

someone ill.

## Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of medical : No action shall be take

responders

: No action shall be taken involving any personal risk or without suitable training.

#### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

## **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: No specific data.

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, waterways, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

## **Precautions for safe handling**

Protective measures

Advice on general occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 08/24/2021 Date of previous issue : 03/22/2018 Version : 3 3/12

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
water value	None.
ammonia, anhydrous	ACGIH TLV (United States, 3/2020).
·	TWA: 25 ppm 8 hours.
	TWA: 17 mg/m³ 8 hours.
	STEL: 35 ppm 15 minutes.
	STEL: 24 mg/m³ 15 minutes.
	NIOSH REL (United States, 10/2016).
	TWA: 25 ppm 10 hours.
	TWA: 18 mg/m³ 10 hours.
	STEL: 35 ppm 15 minutes.
	STEL: 27 mg/m³ 15 minutes.
	OSHA PEL (United States, 5/2018).
	TWA: 50 ppm 8 hours.
	TWA: 35 mg/m³ 8 hours.
Sulfide	None.
phenol	ACGIH TLV (United States, 3/2020). Absorbed through skin.
	TWA: 5 ppm 8 hours.
	TWA: 19 mg/m³ 8 hours.
	NIOSH REL (United States, 10/2016). Absorbed through skin.
	TWA: 5 ppm 10 hours.
	TWA: 19 mg/m³ 10 hours.
	CEIL: 15.6 ppm 15 minutes.
	CEIL: 60 mg/m³ 15 minutes.
	OSHA PEL (United States, 5/2018). Absorbed through skin.
	TWA: 5 ppm 8 hours.
	TWA: 19 mg/m³ 8 hours.
benzene	ACGIH TLV (United States, 3/2020). Absorbed through skin.
	TWA: 0.5 ppm 8 hours.
	TWA: 1.6 mg/m³ 8 hours.
	STEL: 2.5 ppm 15 minutes.
	STEL: 8 mg/m³ 15 minutes.
	OSHA PEL Z2 (United States, 2/2013).
	TWA: 10 ppm 8 hours.
	CEIL: 25 ppm
	AMP: 50 ppm 10 minutes.
	NIOSH REL (United States, 10/2016).
	TWA: 0.1 ppm 10 hours.
	STEL: 1 ppm 15 minutes.
	OSHA PEL (United States, 5/2018).
	TWA: 1 ppm 8 hours.
	STEL: 5 ppm 15 minutes.

# Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Waste Water HF Sinclair **Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. **Skin protection Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. **Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Based on the hazard and potential for exposure, select a respirator that meets the **Respiratory protection** 

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## **Appearance**

Physical state : Liquid.
Color : Clear./Gray.
Odor : Sewer

Odor threshold : Not available.

**pH** : 6 to 9

Melting point: Not available.Boiling point, initial boiling: Not available.

point, and boiling range

Flash point : Not available.
Evaporation rate : Not available.
Flammability : Not available.
Lower and upper explosion : Not available.

limit/flammability limit

Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	23.8	3.2		92.258	12.3	

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Relative vapor density : Not available.

Relative density : 1

**Density**: Not available.

Solubility : Soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature

Decomposition temperature

SADT

SADT

SADT

Not available.

Viscosity

Flow time (ISO 2431)

Not available.

Not available.

Not available.

Particle characteristics

Median particle size : Not applicable.

## **Additional information**

Physical/chemical properties comments

: No additional information.

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : No specific data.

**Incompatible materials** : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

## Information on toxicological effects

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ammonia, anhydrous	LC50 Inhalation Gas.	Rat	9500 ppm	1 hours
	LC50 Inhalation Gas.	Rat	2000 ppm	4 hours
phenol	LD50 Dermal	Rabbit	630 mg/kg	-
	LD50 Dermal	Rat	669 mg/kg	-
	LD50 Oral	Rat	317 mg/kg	-
benzene	LC50 Inhalation Vapor	Rat	13700 ppm	4 hours
	LD50 Oral	Rat	930 mg/kg	-

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
phenol	Eyes - Mild irritant	Rabbit	-	0.5 minutes 5	-
				mg	
	Eyes - Severe irritant	Rabbit	-	5 mg	-
	Skin - Mild irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Rabbit	-	535 mg	-
benzene	Eyes - Moderate irritant	Rabbit	-	88 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Mild irritant	Rabbit	-	24 hours 15	-
				mg	
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	

## **Carcinogenicity**

Product/ingredient name	OSHA	IARC	NTP
phenol	-	3	-
benzene	+	1	Known to be a human carcinogen.

## Specific target organ toxicity (single exposure)

Waste Water HF Sinclair Name Route of **Target organs** Category exposure Sulfide cardiovascular Category 1 system, lungs Category 3 Respiratory tract irritation Category 3 Narcotic effects Category 3 Respiratory tract benzene irritation Category 3 Narcotic effects

## Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
phenol	Category 2	-	kidneys, liver, nervous system
benzene	Category 1	-	blood system, bone marrow, immune system, kidneys, liver

## **Aspiration hazard**

Name	Result
benzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

## Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

		T		I	T
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
ammonia, anhydrous	N/A	N/A	2000	N/A	N/A
Sulfide	N/A	N/A	100	N/A	N/A
phenol	317	630	N/A	N/A	N/A
benzene	930	N/A	N/A	N/A	N/A

# Section 12. Ecological information

## Toxicity

Product/ingredient name	Result	Species	Exposure
		•	
ammonia, anhydrous	Acute EC50 29.2 mg/l Marine water	Algae - Ulva fasciata - Zoea	96 hours
	Acute LC50 2080 μg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 0.53 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 300 μg/l Fresh water	Fish - Hypophthalmichthys nobilis	96 hours
	Chronic NOEC 0.204 mg/l Marine water	Fish - Dicentrarchus labrax	62 days
phenol	Acute EC50 61.1 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 36 mg/l Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Acute EC50 94 mg/l Fresh water	Aquatic plants - Lemna aequinoctialis	96 hours
	Acute EC50 4200 μg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 800 µg/l Marine water	Crustaceans - Archaeomysis kokuboi - Juvenile (Fledgling,	48 hours
		Hatchling, Weanling)	
	Acute LC50 1555 µg/l Fresh water	Fish - Cirrhinus mrigala - Larvae	96 hours
	Chronic NOEC 16 µg/l Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Chronic NOEC 1.5 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 118 µg/l Fresh water	Fish - Oncorhynchus mykiss	90 days
benzene	Acute EC50 29000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 9.23 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Chronic EC10 >1360 mg/l Fresh water	Algae - Desmodesmus subspicatus	96 hours
	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	4 weeks

Persistence and degradability

Date of issue/Date of revision: 08/24/2021Date of previous issue: 03/22/2018Version: 38/12

Product/ingredient name	Test	Result		Dose	Inoculun
phenol benzene	301C Ready Biodegradability - Modified MITI Test (I) 301C Ready Biodegradability - Modified MITI Test (I)	85 % - 14 c		-	-
Product/ingredient name	Aquatic half-life		Photolysis		Biodegradability

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
<mark>w</mark> ater	-1.38	-	low
ammonia, anhydrous	0.0724	-	low
phenol	1.47	647	high
benzene	2.13	11	low

## **Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

## **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# **Section 15. Regulatory information**

U.S. Federal regulations

: United States inventory (TSCA 8b): All components are active or exempted.

Clean Water Act (CWA) 307: phenol; benzene

Clean Water Act (CWA) 311: ammonia, anhydrous; phenol; benzene

Department of homeland security (DHS), Chemical Facility Anti-terrorism Standards (6 CFR 27), Appendix A, **Chemicals of Interest** 

**Security** 

Name	%	Status
ammonia, anhydrous	0 - 0.0025	Listed

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs) SARA 302/304** 

: Listed

**Composition/information on ingredients** 

			SARA 302 TPQ SARA 304 RQ		RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ammonia, anhydrous phenol	0 - 0.0025 0 - 0.0005	Yes. Yes.	500 500 / 10000	-	100 1000	-

**SARA 304 RQ** : 8000000 lbs / 3632000 kg [959472.9 gal / 3632000 L]

**SARA 311/312** 

Classification : Not applicable. **Composition/information on ingredients** 

Name	%	Classification
ammonia, anhydrous	0 - 0.0025	FLAMMABLE GASES - Category 2 GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 HNOC - Corrosive to digestive tract HNOC - Corrosive to respiratory tract
Sulfide	0 - 0.0005	FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
phenol	0 - 0.0005	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 3 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 GERM CELL MUTAGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 HNOC - Corrosive to digestive tract

Date of issue/Date of revision : 08/24/2021 : 03/22/2018 Version: 3 10/12 Date of previous issue

Waste Water **HF Sinclair** 0 - 0.0002 benzene FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A GERM CELL MUTAGENICITY - Category 1B CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 ASPIRATION HAZARD - Category 1

#### **SARA 313**

Not applicable.

## State regulations

**Massachusetts** : None of the components are listed. **New York** : None of the components are listed. **New Jersey** : None of the components are listed. **Pennsylvania** : None of the components are listed.

## California Prop. 65

MARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Benzene	Yes.	Yes.

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

## **Montreal Protocol**

Not listed.

## **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

## **Inventory list**

**Australia** : MI components are listed or exempted. Canada : MI components are listed or exempted. China : All components are listed or exempted. **Europe** : All components are listed or exempted.

Japan inventory (CSCL): All components are listed or exempted. **Japan** 

Japan inventory (ISHL): Not determined.

: Not determined **Malaysia** 

**New Zealand** : MI components are listed or exempted. : MI components are listed or exempted. **Philippines** Republic of Korea All components are listed or exempted. **Taiwan** : MI components are listed or exempted.

Turkey : Not determined.

## Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### **National Fire Protection Association (U.S.A.)**



#### Procedure used to derive the classification

Classification	Justification
Not classified.	

Date of issue/Date of

revision

Date of previous issue

Version

**Key to abbreviations** 

: 08/24/2021

: 03/22/2018

: 3

: ATE = Acute Toxicity Estimate

AMP = Acceptable maximum peak above the acceptable ceiling concentration for an

8-hr shift

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available UN = United Nations

## **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.